

Tenda**User Manual**Tenda Security Camera
IC/IT Series

Please read the instructions to install and quick setup upon the first use.
The manual provides instructions how to install and connect the device. For more information, such as the description of symbols displayed on relevant materials, please visit www.tendacn.com or scan the Product Documents QR code of this manual.

The product name and model are specified on the label of the device.
IC/IT and IT4-LR5 are used for illustrations here unless otherwise specified. The actual product may vary.

Safety Precautions
Before performing an operation, read the operations instructions and precautions to be taken, and follow them to prevent accidents. The warning and danger items in other documents do not cover all the safety precautions that may be followed. They are only supplementary information, and the installation and maintenance personnel need to understand the basic safety precautions to be taken.

- Main power cord shall be installed near the device and easily accessible.

- The power cord shall be connected to the device and disconnected from the device.

- The device is operating environment: Temperature: -10°C ~ 50°C; Humidity: (10% ~ 95%) RH, non-condensing.

- IT series: Operating environment: Temperature: -20°C ~ 60°C; Humidity: (10% ~ 95%) RH, non-condensing; Storage environment: Temperature: -40°C ~ 70°C; Humidity: (30% ~ 95%) RH, non-condensing.

- IT4-LR5: Operating environment: Temperature: -20°C ~ 60°C; Humidity: (10% ~ 95%) RH, non-condensing; Storage environment: Temperature: -40°C ~ 70°C; Humidity: (30% ~ 95%) RH, non-condensing.

- IC series: Operating environment: Temperature: -10°C ~ 50°C; Humidity: (10% ~ 95%) RH, non-condensing; Storage environment: Temperature: -40°C ~ 70°C; Humidity: (30% ~ 95%) RH, non-condensing.

- If such phenomena as smoke, abnormal sound or smell appear when you use the device, immediately stop using it and disconnect its power supply, unplug all connected cables, and contact the service center.

- Disassembling or modifying the device or its accessories without authorization voids the warranty, and might cause safety hazards.

- For wall/ceiling/pendant mounting, the camera is suitable for mounting at heights >2m.

Get support and services

Scan the Product Documents QR code to get related documents for more information.



The specific product model can be found on the label of the device.

Product Documents (such as quick installation guide (multiple version), user guide and installation)



Product Documents (such as quick installation guide (multiple version), user guide and installation)

support@tendacn.com (Deutsch)
support@tendacn.com (Español)
support@tendacn.com (Français)
support@tendacn.com (Italiano)
support@tendacn.com (English)

support@tendacn.com (Portuguese)

support@tendacn.com (Russian)

support@tendacn.com (Spanish)

support@tendacn.com (United Kingdom)

support@tendacn.com (Chinese)

support@tendacn.com (Arabic)

support@tendacn.com (Korean)

support@tendacn.com (Japanese)

support@tendacn.com (Chinese)

support@tendacn.com (Chinese)