

TECHNICAL ACCEPTANCE  
CERTIFICATE

CERTIFICAT D'ACCEPTABILITÉ  
TECHNIQUE

CERTIFICATION No. No. DE CERTIFICATION	2468C-11ACAP22W			
TELEFICATION No. No. DE TELEFICATION	212170029/AA/00			
TEST SITE No. No. DE LABORATOIRE	10807A			
ISSUED TO DÉLIVRÉ A	Zyxel Communications Corporation No. 2, Industry East Road IX, Science Park Hsinchu Taiwan			
TYPE OF EQUIPMENT GENRE DE MATÉRIEL	Local Area Network (LAN) Device Spread Spectrum or Digital Device (2400-2483.5 MHz)			
TRADE NAME AND MODEL MARQUE ET MODELE	ZYXEL / WAC500H			
CERTIFIED TO CERTIFIÉ SELON LE	SPECIFICATION CAHIER DES CHARGES	RSS-102 RSS-247	ISSUE EDITION	5 2

Certification of equipment means only that the equipment has met the requirements of the above-noted specification. Licence applications, where applicable to use certified equipment, are acted on accordingly by the ISED issuing office and will depend on the existing radio environment, service and location of operation. This certificate is issued on condition that the holder complies and will continue to comply with the requirements and procedures issued by ISED. The equipment for which this certificate is issued shall not be manufactured, imported, distributed, leased, offered for sale or sold unless the equipment complies with the applicable technical specifications and procedures issued by ISED.

La certification du matériel signifie seulement que le matériel a satisfait aux exigences de la norme indiquée ci-dessus. Les demandes de licences nécessaires pour l'utilisation du matériel certifié sont traitées en conséquence par le bureau de délivrance d'ISDE et dépendent des conditions radio ambiantes, du service et de l'emplacement d'exploitation. Le présent certificat est délivré à la condition que le titulaire satisfasse et continue de satisfaire aux exigences et aux procédures d'ISDE. Le matériel à l'égard duquel le présent certificat est délivré ne doit pas être fabriqué, importé, distribué, loué, mis en vente ou vendu à moins d'être conforme aux procédures et aux spécifications techniques applicables publiées par ISDE.


ISSUED BY TELEFICATION BV (NL0001), RECOGNIZED CERTIFICATION BODY BY INNOVATION, SCIENCE AND ECONOMIC DEVELOPMENT CANADA, ACCORDING THE CANADIAN CERTIFICATION BODY SCHEME (CB-02).  
DÉLIVRÉ PAR TELEFICATION BV (NL0001), ORGANISME DE CERTIFICATION RECONNU PAR INNOVATION, SCIENCES ET DÉVELOPPEMENT ÉCONOMIQUE CANADA, SELON LE SYSTÈME D'ORGANISME DE CERTIFICATION DE CANADA (CB-02).

*I hereby attest that the subject equipment was tested and found in compliance with the above-noted specification.  
J'atteste, par la présente, que le matériel a fait l'objet d'essai et a été jugé conforme à la spécification ci-dessus*

DATE 29 Jan 2021 BY

Gürhan Vural  
Product Assessor

This certificate has one annex.



TEST REPORTS  
RAPPORTAGE DE TEST

- International Certification Corp.: CR062401AC, 07 October 2020
- International Certification Corp.: CR062401AN, 07 October 2020
- International Certification Corp.: CR062401CO, 07 October 2020
- International Certification Corp.: CA062401, 07 October 2020
- International Certification Corp.: CR062401-01AN, 21 January 2021
- International Certification Corp.: CZ062401-01, 21 January 2021
- International Certification Corp.: CA062401-01, 21 January 2021

FREQUENCY RANGE BANDE DE FRÉQUENCES	EMISSION DESIGNATION DESIGNATION D'ÉMISSION	R.F. POWER RATING PUISSANCE NOMINALE H.F.
2412-2462 MHz	14M8G1D	0.466 W
2412-2462 MHz	23M6D1D	0.358 W
2422-2452 MHz	35M9D1D	0.091 W
5180-5240 MHz	17M6D1D	0.098 W
5190-5230 MHz	36M2D1D	0.188 W
5210 MHz	75M8D1D	0.106 W
5745-5825 MHz	24M5D1D	0.472 W
5755-5795 MHz	55M9D1D	0.518 W
5775 MHz	76M1D1D	0.221 W
5260-5320 MHz	17M6D1D	0.106 W
5270-5310 MHz	36M0D1D	0.105 W
5290 MHz	75M7D1D	0.057 W
5500-5580 MHz	17M7D1D	0.201 W
5510-5550 MHz	36M1D1D	0.243 W
5530 MHz	75M7D1D	0.071 W
5660-5720 MHz	17M6D1D	0.164 W
5670-5710 MHz	36M0D1D	0.204 W
5690 MHz	72M9D1D	0.208 W

ANTENNA INFORMATION  
INFORMATION D'ANTENNE

PIFA antenna, max gain of 0 dBi at 2.4 GHz and max gain of 2.5 dBi at 5 GHz

REMARKS  
REMARQUES

Class III Permissive Change : Only firmware is modified to enable U-NII band 5250-5350 MHz, 5470-5600 MHz, and 5650-5725 MHz.

Device supports 2TX MIMO and beamforming capability.