



Software Release Note
NebulaFlex Switch GS2220 Series

Date: June 18, 2021

Zyxel NebulaFlex Switch GS2220 Series

V4.70(AB__.4)C0 Release Note

Date: June 18, 2021

This document describes the features in the GS2220 for its 4.70(AB__.4)C0 release.

GS2220 series is a hybrid switch with NebulaFlex technology to support operation in either Standalone mode or Nebula cloud management mode.

Supported Platforms

Support Platform	Firmware version	Boot Version
Zyxel GS2220-10	V4.70(ABRO.4)C0	V1.00 09/20/2019
Zyxel GS2220-10HP	V4.70(ABRP.4)C0	V1.00 09/20/2019
Zyxel GS2220-28	V4.70(ABRQ.4)C0	V1.00 09/20/2019
Zyxel GS2220-28HP	V4.70(ABRR.4)C0	V1.00 09/20/2019
Zyxel GS2220-50	V4.70(ABRS.4)C0	V1.00 09/20/2019
Zyxel GS2220-50HP	V4.70(ABRT.4)C0	V1.00 09/20/2019

New Feature and Enhancements

1. Support new PoE MCU for GS2220-10HP. (PoE model only)

Bug fix

None.

Known Issue

Known Issue	Cloud	Stacking	Standalone
1. [Bandwidth Control] Ingress rate limit of TCP traffic is inaccurate when value limits above 300M.	V	-	V

Known Issue	Cloud	Stacking	Standalone
2. [IP source guard] Create an IP static binding first, and then send an illegal IP traffic with the same MAC address but different IP address. The illegal IP traffic cannot be filtered.	-	-	V
3. [Green Ethernet] The status of short-reach will display incorrectly.	-	-	V
4. [Diagnostic] The accuracy of cable diagnostic is +- 15m. When without cables, the value of distance to fault would not be 0.	V	-	V
5. [Diagnostic] Cable Diagnostic is not supported on 10M-Full Duplex connection. A message "unknown" will be displayed on the Diagnostic screen when the operation is executed.	V	-	V
6. [Panel LED] The link LED will turn on when plug-in SFP-100TX or SFP-1000T while cable is not connected.	V	-	V
7. [VLAN] The VLAN Mapping doesn't work with untagged frame.	-	-	V

Limitation of Settings:

Limitation of Setting	Cloud	Stacking	Standalone
1. 802.1Q Static VLANs	1k	-	1K
2. Static MAC forwarding entry	256	-	256
3. MAC filtering entry	256	-	256
4. Cluster member	-	-	24
5. Port-security max address-limit number	-	-	16K

Limitation of Setting	Cloud	Stacking	Standalone
6. Syslog server entry	2	-	4
7. MAC table	16k	-	16k
8. Multicast group	1k	-	1k
9. ACL	128	-	256
10. DHCP Relay Entry	-	-	16
11. Static ARP entry	-	-	256
12. Static route max entry	-	-	32
13. Trunk groups	5/14/16	-	5/14/16
14. Per trunk group port number	8	-	8
15. MSTP instance	-	-	0-16
16. Voice VLAN OUI entry	10	-	10
17. ZON neighbor per-port maximum clients	10	-	10

Change History

- V4.70(AB__.3) | 06/01/2021
- V4.70(AB__.2) | 03/03/2021
- V4.70(AB__.1) | 01/20/2021
- V4.70(AB__.0) | 08/04/2020
- V4.60(AB__.0) | 10/10/2019